

Air -/ Water Heat Exchanger RK 2192-230V



Product Description

Order Number:	2192000
Colour:	RAL 7035
Protection category IP (IEC 60 529):	IP 44
Note:	With thermostatic solinoid controlled valve
Approvals:	CE
Customs tariff number:	84195000
Material housing:	Mild steel, powder coated

Technical data RK 2192-230V

Cooling capacity L35W10 (200 l/h):	1 kW @ 50 Hz
	1 kW @ 60 Hz
Cooling capacity L35W10 (500 l/h):	1,2 kW @ 50 Hz
	1,2 kW @ 60 Hz
Refrigerant:	Water, light oils or similar
Operating temperature range:	+1°C - +72°C
Max. air volume flow:	180 m ³ /h
Mounting:	19" mounting
Dimensions (H x W x D):	2HE x 443 x 408 mm
Weight:	13 kg
Rated operating voltage / frequency:	230 V 50/60 Hz ~N
Rated current:	0.4 A
Starting current:	1 A
Power consumption:	90 W
Max. Working pressure water circuit:	10 bar
Water connection:	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 10 mm
Fuse rating:	4 A (T)
Connection:	Plug


Click the graphics to download the originals.

More CAD graphics can be found on our [Products Downloads page](#).


> [Overview product group Air-Water Heat Exchangers](#)

Performance Graph:

? T = Temperature difference between air intake and cooling
 P = Cooling capacity



click image to enlarge

Airflow diagram:


click image to enlarge

Cutout diagram:

click image to enlarge

[Datasheet](#) created 23.07.2015 (10:14:25). Technical rights reserved.