

Cabinet cooling units - roof mounted KG 4482-120V



Product Description

Brand name:	SoliTherm TOP
Order Number:	44821001
Colour:	RAL 7035
Protection category IP (IEC 60 529):	External circuit: IP 24 Internal circuit: IP 54
Add-ons:	Stainless steel housing, part no. 4482102
Approvals:	CE, cURus
Customs tariff number:	84158200
Material housing:	Mild steel, powder coated

Technical data KG 4482-120V

Cooling capacity / output L35L35:	460 W @ 60 Hz
Cooling capacity / output L35L50:	280 W @ 60 Hz
Compressor:	Rotary piston compressor
Refrigerant:	R134a
Refrigerant charge:	175 g
Operating temperature range:	+20°C - +50°C
Max. air volume flow:	Ambient air circuit: 250 m ³ /h Cabinet air circuit: 140 m ³ /h
Mounting:	Roof mounted
Dimensions (H x W x D):	230 x 430 x 330 mm
Weight:	23 kg
Cut out dimensions:	142 x 98 mm / 142 x 147.5 mm
Rated operating voltage / frequency:	120 V - 60 Hz ~N
Rated current L35L35:	4.2 A @ 60 Hz
Starting current:	17 A
Max. current:	5.2 A
Power consumption L35L35:	480 W @ 60 Hz
Max. power consumption:	590 W
Fuse rating:	6 A (T)
Connection:	Connection terminal block


Click the graphics to download the originals.

More CAD graphics can be found on our [Products Downloads page](#).


> [Overview product group Cooling units - roof mounted](#)

Performance Graph:


T = Ambient temperature
 P = Cooling capacity



[click image to enlarge](#)

Airflow diagram:


[click image to enlarge](#)

Cutout diagram:


[click image to enlarge](#)

[Datasheet](#) created 22.07.2015 (12:44:21). Technical rights reserved.